



EVERY **JOURNEY**
HAS A **DESTINATION**

PRODUCT
CATALOGUE



GERMAN TECHNOLOGY
TESTED IN JAPAN & EUROPE

COMPANY PROFILE

Ghandhara Tyre & Rubber Company Limited (formerly known as The General Tyre and Rubber Company of Pakistan Limited) came into existence in 1963, at Landhi Karachi and commenced its production in July 1964.

The Company was then established by General Tire International Corporation (GTIC) of USA, with a total capacity of only 120,000 tyres per annum.

In 1977, GTIC sold 90% of their shares to the present owner M/s Bibojee Services Ltd. and retained 10% of the ownership. In 1985, the Company completed a major expansion, which took the capacity to 600,000 tyres annually.

In 1987, Continental AG, Germany's number one tyre manufacturer purchased GTIC and became the 10% owner. It provides Technical Assistance to the company under a program, which includes training of our people, formulations, recipe, and selection of equipment and acquiring of raw materials from approved suppliers. The company under this agreement with Continental is bound to follow all rules and regulations provided by Continental including the given quality standards.

Since the takeover of GTIC by Continental, they own the brand name GENERAL which currently carries the highest top of the mind position in the market and has a very high recall. Now with over five decades of experience in the art of making tyres, the brand name is synonymous with quality and is considered a heritage brand.

The dynamics of the market is changing and the middle class is entering the car market. They are looking for a different dynamic when it comes to purchasing the tyres. The company as a strategic move to get a major share of this new and growing market and has decided to modernize the outlook of the brand name from General Tyre to "GTR Tyre" as a parallel brand to capture the imagination of this new class of enthusiast motorists mainly youth which will find the name classy, easy to use and a certain dynamism about it. A modern name with a modern look.

Being a Public Listed Company, the current main

sponsors of the Company are: (i) Bibojee Services (Private) Ltd. and (ii) Pak Kuwait Investment Company (PKIC) (iii) National Investment Trust (NIT) while the remaining shares are held by the general public.

The current capacity of the Company stands at 24 million for automotive tyres per annum. While the motorcycle plant capacity is 1.6 million tyres per annum. The company produces tyre sizes and patterns that cover almost 70% of the sizes in demand in Pakistan.

It is the first & largest automotive tyre manufacturer in the country producing steel belted tubeless radial tyres for cars, SUVs and 4x4 vehicles. While bias or cross ply tyres for some light trucks, trucks/buses, tractors, rickshaw, motorcycle and now OTR including excavator tyres.

The Company caters four different markets. These are:

- The Original Equipment Manufacturers (vehicle assemblers)
- The Replacement or the After market
- Government Departments/Institutions
- The Export Market

GTR sells its tyres in replacement market through more than 190 nationwide authorized dealers/distributors most of whom have been working with GTR for more than three generations setting a milestone on customer loyalty and satisfaction.

It is the largest tyre supplier to all OEMs meeting almost 80% of their requirement. To meet the quality standards of OE, tyres are tested in Japan & Europe. It has been exporting tyres to Afghanistan, Yemen, Botswana, Syria, Nepal & Bangladesh. It has also been engaged in manufacturing & exporting tyres (FAST) for Formula III racing car to UK, Italy & Sweden from 1988-1998.

It has Head Office / main warehouse in Karachi while branch offices / warehouses are located in four major cities of Pakistan namely Islamabad, Lahore, Multan and Sukkur. Company gives comprehensive warranty on its manufactured products.

EVERY JOURNEY HAS A DESTINATION

VISION

To be the leader in tyre technology by building the Company's image through quality improvement, competitive prices, customer satisfaction and meeting social obligations.

MISSION

- To offer quality products at competitive prices to our customers.
- To endeavor to be the market leader by enhancing market share, consistently improving efficiency and the quality of our products.
- To improve performance in all operating areas, so that profitability increases thereby ensuring growth for the company and increasing return to the stakeholders.
- To create a conducive working environment leading to enhanced productivity, job satisfaction and personal development of our employees.
- To discharge its obligation to society and environment by contributing to social welfare and adopting environmental friendly practices and processes.

QUALITY POLICY

We are a company of dedicated people who enjoy working as a team and with our customers in an enterprise committed to quality.

We will continually strive to bring improvement in our products, services and quality management system to meet or exceed our customer needs and expectations.

We will work within the Framework of legal and regulatory requirements.

HSE POLICY

“Health, Safety and Environment”

Ghandhara Tyre & Rubber Company Limited recognizes Occupational Health, Safety And Environment as one of its guiding principles and a key component of our Corporate social responsibility.

We are committed to protect environment specifically prevention of pollution and ensure a safe and healthy working environment with consultation and participation of our stake holders by minimizing HSE impacts and risk levels as a result of business activities. We are committed to comply with all applicable Occupational HSE legislations and regulations. We ensure required HSE standards and procedures are established and implemented. We train and motivate all our employees to empower them to play an active role in company's pledge to its HSE policy.

We set demanding targets and measure progress to ensure continual improvement in HSE performance. We follow the approach of Reduce-Reuse-Recycle for resource conservation.

EVERY JOURNEY HAS A DESTINATION

PASSENGER CAR RADIAL TYRE

EVERY JOURNEY HAS A DESTINATION



PASSENGER CAR RADIAL TYRE

BG THUNDER MAX

Asymmetric tyre designed for high performance on all surfaces

Features

- Asymmetric high performance with wide circumferential grooves
- New generation tread pattern
- Strong casing and steel belted
- 'V' rated tyre for speed upto 240 km/hr
- Better uniformity
- Full cap ply

Benefits

- Excellent performance on wet & dry surfaces
- Evenly good for traction and braking
- Ride comfort
- Even wear
- Safety & long life

E24



PRODUCT INFORMATION

| | | | |
|-------------------------------|---|-------------|-------------|
| Size | 195/65 R15 | 205/55 R16 | 215/50 R17 |
| Speed Rating | H | H | V |
| Pattern | RIB | RIB | RIB |
| Load Index | 91 | 91 | 91 |
| MAX INFLATED DIMENSION | | | |
| Overall Diameter (mm) | 640 | 635 | 650 |
| Overall Width (mm) | 205 | 215 | 220 |
| RIM | | | |
| Size/Code | 6.0"J x 15" | 6.5"J x 16" | 7.0"J x 17" |
| LOAD AND INFLATION | | | |
| Max Load (kg) | 615 | 615 | 615 |
| Max Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | | |

PASSENGER CAR RADIAL TYRE

BG LUXO PLUS

Asymmetric design tyre with multiple circumferential ribs for excellent ride and comfort

Features

- Asymmetric design tyre with wide grooves
- Multiple circumferential ribs
- Strong casing
- 'H' rated tyre for speed upto 210 km/hr
- Full cap ply

Benefits

- High performance tyre in all weather conditions
- Fantastic handling & cornering characteristic
- Excellent ride comfort
- For safety & longer life

E24



PRODUCT INFORMATION

| | | |
|-------------------------------|---|------------|
| Size | 215/55 R16 | 195/60 R16 |
| Speed Rating | H | H |
| Pattern | RIB | RIB |
| Load Index | 93 | 89 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 645 | 643 |
| Overall Width (mm) | 220 | 196 |
| RIM | | |
| Size/Code | 7"J x 16" | 6"J x 16" |
| LOAD AND INFLATION | | |
| Max Load (kg) | 650 | 580 |
| Max Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

PASSENGER CAR RADIAL TYRE

BG FALCON

New generation high performance tyre provides excellent ride comfort

Features

- High performance tyre with wide circumferential grooves
- New generation tread pattern
- Strong casing and steel belted
- Heat and abrasion resistance
- Low noise level and low rolling resistance

Benefits

- Provides excellent performance on wet & dry surfaces
- Evenly good for traction and braking
- Provides ride comfort
- Helps in even wear
- Provides more safety & long life



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 185/65 R15 |
| Speed Rating | H |
| Pattern | R1B |
| Load Index | 88 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 625 |
| Overall Width (mm) | 192 |
| RIM | |
| Size/Code | 5.5" J x 15" |
| LOAD AND INFLATION | |
| Max Load (kg) | 560 |
| Max Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

PASSENGER CAR RADIAL TYRE

BG TRAKO PLUS

Built for high performance & comfortable ride

Features

- Steel belted radial tyre
- New generation tread pattern
- Soft yet tough construction
- 'H' rated tyre for speed upto 210 km/hr
- Full cap ply

Benefits

- Exceptional wear & built for high performance
- Optimizes handling & speed
- Comfortable & smooth ride
- Superb cornering stability and grip
- For safety & longer life

E24



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 185/60 R 15 |
| Speed Rating | H |
| Pattern | RIB |
| Load Index | 84 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 605 |
| Overall Width (mm) | 185 |
| RIM | |
| Size/Code | 5.5J x 15" |
| LOAD AND INFLATION | |
| Max Load (kg) | 500 |
| Max Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

PASSENGER CAR RADIAL TYRE

BG PERFORMA

Latest tyre design provides comfort ride and better road grip

Features

- New generation tread pattern
- Strong casing and steel belted
- 'T' rated tyre for speed up to 190km/hr
- Heat resistance and abrasion resistant

Benefits

- Excellent performance in all seasons
- Evenly good for traction and braking
- Provide comfortable & smooth ride
- Even and good wear
- Safety & long life



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | T75/65 R14 |
| Speed Rating | T |
| Pattern | RIB |
| Load Index | 82 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 582 |
| Overall Width (mm) | 176 |
| RIM | |
| Size/Code | 5.0" J x 12" |
| LOAD AND INFLATION | |
| Max Load (kg) | 475 |
| Max Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

PASSENGER CAR RADIAL TYRE

BG TRAKER

Latest pattern tyre that performs well on local road condition

Features

- Latest European Design
- Smooth rolling & steering stability
- 'T' rated tyre for speed up to 190km/hr
- Heat resistance and abrasion resistant

Benefits

- Provides excellent performance on all surfaces
- Evenly good for traction and braking
- Provides comfortable & smooth ride
- For safety & long life



PRODUCT INFORMATION

| | | |
|-------------------------------|---|-------------|
| Size | 155/70 R12 | 165/70 R12 |
| Speed Rating | T | T |
| Pattern | RIB | RIB |
| Load Index | 73 | 77 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 525 | 535 |
| Overall Width (mm) | 155 | 165 |
| RIM | | |
| Size/Code | 4.5"J x 12" | 5.0"J x 12" |
| LOAD AND INFLATION | | |
| Max Load (kg) | 365 | 412 |
| Max Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

PASSENGER CAR RADIAL TYRE

BG ECONO

Passenger car radial tyre provides better fuel economy & ride comfort

Features

- Computerised tread pattern
- Strong casing and steel belted
- 'T' rated tyre for speed up to 190km/hr
- Heat resistance and abrasion resistant

Benefits

- Provides better fuel economy
- Provides evenly good traction and braking
- Provides comfortable & smooth ride
- For even wear, safety & long life



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 145/70 R12 |
| Speed Rating | T |
| Pattern | RIB |
| Load Index | 69 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 512 |
| Overall Width (mm) | 144 |
| RIM | |
| Size/Code | 4.5" J x 12" |
| LOAD AND INFLATION | |
| Max Load (kg) | 325 |
| Max Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

PASSENGER CAR RADIAL TYRE

BG TEMPO PLUS

Passenger car radial tyre for better road grip & smooth ride

Features

- Solid center steering rib
- High impact resistant tyre
- Open tread shoulder groove
- Latest European design
- Full cap ply

Benefits

- Excellent straight line stability for better handling
- Provides smooth & comfortable ride
- Outstanding grip on wet surfaces
- Superb precision steering response
- For safety & longer life



PRODUCT INFORMATION

| | | |
|-------------------------------|---|-------------|
| Size | 155/70 R12 | 165/70 R12 |
| Speed Rating | T | T |
| Pattern | RIB | RIB |
| Load Index | 73 | 77 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 523 | 536 |
| Overall Width (mm) | 155 | 165 |
| RIM | | |
| Size/Code | 4.5"J x 12" | 5.0"J x 12" |
| LOAD AND INFLATION | | |
| Max Load (kg) | 365 | 412 |
| Max Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

PASSENGER CAR RADIAL TYRE

EURO STAR

An ultimate design for a comfortable ride and good grip

Features

- New generation computerized tread pattern
- Wide grooves, long sipes for wet and dry traction
- Radial polyester cord ply
- 'T'/'H' rated tyres for speed upto 190/210 km/hr
- High speed optimized belt system
- Full cap ply

Benefits

- Heat resistance and abrasion resistance
- Low noise level and low rolling resistance
- Softer ride & safe handling
- For safety and longer life

E24



PRODUCT INFORMATION

| | | |
|-------------------------------|---|-------------|
| Size | 175/65 R15 | 195/65 R15 |
| Speed Rating | T | H |
| Pattern | RIB | RIB |
| Load Index | 84 | 91 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 615 | 640 |
| Overall Width (mm) | 180 | 205 |
| RIM | | |
| Size/Code | 5.0"J x 15" | 6.0"J x 15" |
| LOAD AND INFLATION | | |
| Max Load (kg) | 500 | 615 |
| Max Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

PASSENGER CAR RADIAL TYRE

EURO KRUZE

Directional pattern tyre for an excellent road grip

Features

- Two circumferential rib & one solid centre rib
- Wide circumferential & lateral drainage grooves
- Multiple tread sipes
- Four wide circumferential grooves
- 'T' rated tyre for speed upto 190 km/hr
- Full cap ply

Benefits

- For directional stability & precise steering response
- Provides excellent performance on wet surfaces
- For better road grip & control
- Low noise with a comfortable ride
- For safety & longer life

E24



PRODUCT INFORMATION

| | | |
|-------------------------------|---|-------------|
| Size | 165/65 R13 | 185/65 R14 |
| Speed Rating | T | T |
| Pattern | RIB | RIB |
| Load Index | 77 | 86 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 545 | 589 |
| Overall Width (mm) | 165 | 186 |
| RIM | | |
| Size/Code | 5.0"J x 13" | 5.5"J x 14" |
| LOAD AND INFLATION | | |
| Max Load (kg) | 412 | 530 |
| Max Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

PASSENGER CAR RADIAL TYRE

EURO TYCOON

Latest tyre design for an excellent road grip

Features

- Latest European design
- Smooth rolling and steering stability
- Ride comfort and excellent traction
- 'T' rated tyre for speed upto 190 km/hr
- Full cap ply

Benefits

- Excellent performance on wet & dry surfaces
- Low rolling resistance & low noise
- Provides excellent road grip
- For safety & longer life

E24



PRODUCT INFORMATION

| | | | |
|-------------------------------|---|-------------|-------------|
| Size | 175/70 R13 | 145/80 R13 | 165/65 R14 |
| Speed Rating | T | T | T |
| Pattern | RIB | RIB | RIB |
| Load Index | 82 | 79 | 75 |
| MAX INFLATED DIMENSION | | | |
| Overall Diameter (mm) | 575 | 572 | 563 |
| Overall Width (mm) | 175 | 164 | 143 |
| RIM | | | |
| Size/Code | 5.0"J x 13" | 5.0"J x 14" | 4.0"J x 13" |
| LOAD AND INFLATION | | | |
| Max Load (kg) | 475 | 437 | 387 |
| Max Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | | |

PASSENGER CAR RADIAL TYRE

EURO GLIDE

Latest directional pattern tyre for a comfortable and smooth drive

Features

- Latest European design
- High speed optimized belt system
- Radial polyester cord body
- 'T' rated tyre for speed upto 190 km/hr
- Full cap ply

Benefits

- Excellent performance on wet & dry surfaces
- Low rolling resistance & low noise
- Provides excellent road grip
- For safety & longer life



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 185/70R13 |
| Speed Rating | T |
| Pattern | RIB |
| Load Index | 86 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 590 |
| Overall Width (mm) | 180 |
| RIM | |
| Size/Code | 5.5"J x 13" |
| LOAD AND INFLATION | |
| Max Load (kg) | 530 |
| Max Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

PASSENGER CAR RADIAL TYRE

EURO KOMPACT

Non-directional tubeless radial tyre for
Suzuki Mehran, Alto and Daihatsu Cuore

Features

- Latest European design
- Stylized black sidewall
- "T" rated tyre for speed upto 190 km/hr
- Full cap ply

Benefits

- Provides comfortable & smooth ride
- Performance in all seasons
- Precise handling
- Gives a sporty appearance
- For safety and longer life



PRODUCT INFORMATION

| | | | |
|-------------------------------|---|-------------|-------------|
| Size | 145/80 R12 | 155/70 R12 | 165/70 R12 |
| Speed Rating | T | T | T |
| Pattern | RIB | RIB | RIB |
| Load Index | 74 | 73 | 77 |
| MAX INFLATED DIMENSION | | | |
| Overall Diameter (mm) | 535 | 523 | 536 |
| Overall Width (mm) | 150 | 155 | 165 |
| RIM | | | |
| Size/Code | 4.0"J x 12" | 4.5"J x 12" | 5.0"J x 12" |
| LOAD AND INFLATION | | | |
| Max Load (kg) | 375 | 365 | 412 |
| Max Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | | |

PASSENGER CAR RADIAL TYRE

RADIAL ST

The tyre that looks good and rides well on our roads in all weather conditions.

Features

- Computer designed tread
- Mud and snow rated
- Lateral slots
- 'T' rated for speed upto 190 km/hr
- Full cap ply

Benefits

- Quiet and comfortable ride
- Performance in all seasons
- Provides excellent wet & dry traction
- For safety and longer life



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 145/70 TR12 |
| Speed Rating | T |
| Pattern | RIB |
| Load Index | 65 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 515 |
| Overall Width (mm) | 150 |
| RIM | |
| Size/Code | 4.50"J x 12" |
| LOAD AND INFLATION | |
| Max Load (kg) | 290 |
| Max Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

PASSENGER CAR RADIAL TYRE

XP 2000 II

Steel belted tubeless radial tyre

Features

- Tread designed for wider foot prints
- Mud & Snow rated
- 'T' rated for speed upto 190 km/hr
- Full cap ply

Benefits

- Tough and long lasting with sipe angles staggered to reduce noise
- Excellent performance in all seasons
- For safety and longer life



PRODUCT INFORMATION

| | | | |
|-------------------------------|---|-------------|------------|
| Size | 155/80 R13 | 165/80 R13 | 175/70 R14 |
| Speed Rating | T | T | T |
| Pattern | RIB | RIB | RIB |
| Load Index | 79 | 83 | 84 |
| MAX INFLATED DIMENSION | | | |
| Overall Diameter (mm) | 575 | 600 | 605 |
| Overall Width (mm) | 155 | 175 | 185 |
| RIM | | | |
| Size/Code | 4.5"J x 13" | 4.5"J x 13" | 5"J x 14" |
| LOAD AND INFLATION | | | |
| Max Load (kg) | 435 | 485 | 500 |
| Max Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | | |

LIGHT TRUCK BIAS TYRE

EVERY JOURNEY HAS A DESTINATION



LIGHT TRUCK BIAS TYRE

POWER JET COMMERCIAL (PJC)

The tyre designed for vans & pickups

Features

- Computer designed rib saw tooth pattern
- Flat tread

Benefits

- Quiet operation
- Designed for an added traction
- Engineered for long and even wear
- Helps maintain handling and steering control



PRODUCT INFORMATION

| | | |
|-------------------------------|---|------------|
| Size | 4.50-12 | 6.50-14 |
| Load Range | D | E |
| Pattern | RIB | RIB |
| Ply Rating | 8 | 10 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 550 | 700 |
| Overall Width (mm) | 135 | 190 |
| TUBE | | |
| Size/Code | 4.50-12 | 6.50-14 |
| Valve Code | TR-13 | TR-13 |
| RIM | | |
| Size/Code | 4.0" x 12" | 5.0" x 14" |
| LOAD AND INFLATION | | |
| Single | | |
| Maximum Load (kg) | 415 | 925 |
| Dual | | |
| Maximum Load (kg) | - | 875 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

*Super Power Jet Commercial (Spjc)

LIGHT TRUCK BIAS TYRE

CHIEF

The tyre designed for vans & pickups

Features

- Multi rib design
- Strong nylon casing
- Heat resistant tread rubber

Benefits

- Excellent mileage and traction
- Low rolling resistance and good traction
- Lesser heat development
- High casing reliability



PRODUCT INFORMATION

| | | |
|-------------------------------|---|------------|
| Size | 4.50-12 | 6.50-14 |
| Load Range | D | E |
| Pattern | RIB | RIB |
| Ply Rating | 8 | 10 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 548 | 700 |
| Overall Width (mm) | 138 | 190 |
| TUBE | | |
| Size/Code | 4.50-12 | 6.50-14 |
| Valve Code | TR-13 | TR-13 |
| RIM | | |
| Size/Code | 4.0" x 12" | 5.0" x 14" |
| LOAD AND INFLATION | | |
| Single | | |
| Maximum Load (kg) | 412 | 930 |
| Dual | | |
| Maximum Load (kg) | - | 875 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

LIGHT TRUCK BIAS TYRE

POWER RIB

Rib pattern tyre designed for better steering control & grip

Features

- Computer designed rib saw tooth
- Multi rib design
- Heat resistant tread rubber
- Flat tread

Benefits

- For smooth & quiet operation
- Enhanced added traction
- Engineered for long and even wear
- Helps maintain handling and steering control



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 6.00 - 14LT |
| Load Range | D |
| Pattern | RIB |
| Ply Rating | 8 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 672 |
| Overall Width (mm) | 170 |
| TUBE | |
| Size/Code | 6.00 / 6.50 - 14 |
| Valve Code | TR-13 |
| RIM | |
| Size/Code | 4.5" x 14" |
| LOAD AND INFLATION | |
| Single | |
| Maximum Load (kg) | 750 |
| Dual | |
| Maximum Load (kg) | 710 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

LIGHT TRUCK BIAS TYRE

TRACTION RIB (TR)

The most popular rib pattern for all position light truck tyres

Features

- Rib type pattern
- Flat tread
- Strong nylon casing

Benefits

- Tough and long lasting
- Minimum heat build-up
- Engineered for excellent steerability at front and strong traction at drive position



PRODUCT INFORMATION

| | | |
|-------------------------------|---|------------|
| Size | 6.50-16 | 7.00-16 |
| Load Range | E/G | G |
| Pattern | RIB | RIB |
| Ply Rating | 10/14 | 14 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 755 | 794 |
| Overall Width (mm) | 200 | |
| TUBE | | |
| Size/Code | 6.50-16 | 7.00-16 |
| Valve Code | TR-75A | TR-75A |
| RIM | | |
| Size/Code | 5.0" x 16" | 5.5" x 16" |
| FLAP | | |
| Code | 406-180LT | 406-180LT |
| LOAD AND INFLATION | | |
| Single | | |
| Maximum Load (kg) | 1050/1100 | 1230 |
| Dual | | |
| Maximum Load (kg) | - | 875 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

LIGHT TRUCK BIAS TYRE

NON-DIRECTIONAL (ND)

The most popular rib pattern for all position light truck tyres

Features

- Rib type pattern
- Flat tread

Benefits

- Tough and long lasting
- Minimum heat build-up
- Engineered for excellent steerability at front and strong traction at drive position



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 6.00-16 |
| Load Range | C/D |
| Pattern | LUG |
| Ply Rating | 6/8 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 750 |
| Overall Width (mm) | 175 |
| TUBE | |
| Size/Code | 6.00-16 |
| Valve Code | TR-15 |
| RIM | |
| Size/Code | 4.50" x 16" |
| LOAD AND INFLATION | |
| Single | |
| Maximum Load (kg) | 705/820 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

LIGHT TRUCK BIAS TYRE

GLT II

A tyre designed to perform in conditions where extra traction is required

Features

- Tread design in rib/lug tyre pattern
- Non directional

Benefits

- For powerful traction, tough & long lasting
- Wider footprint for good stability
- Designed with high void-to-lug ratio for traction
Rib and sipe angles staggered to reduce noise



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 7.50-16 |
| Load Range | D/G |
| Pattern | RIB/LUG |
| Ply Rating | 8/14 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 827/825 |
| Overall Width (mm) | 217/215 |
| TUBE | |
| Size/Code | 7.00/7.50-16 |
| Valve Code | TR-177A |
| RIM | |
| Size/Code | 6.0" x 16" |
| FLAP | |
| Code | 406-180LT |
| LOAD AND INFLATION | |
| Single | |
| Maximum Load (kg) | 1175/1510 |
| Dual | |
| Maximum Load (kg) | 1120/1440 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

LIGHT TRUCK BIAS TYRE

LOAD STAR

Multifunctional tread design provides better road grip & traction

Features

- Nylon construction
- Heat resistant tread compound
- Designed deep lugs

Benefits

- Helps in tough and long lasting service
- Provides cooler running
- Provides excellent traction for drive wheel



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 5.00-12 |
| Load Range | F |
| Pattern | LUG |
| Ply Rating | 12 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 575 |
| Overall Width (mm) | 150 |
| TUBE | |
| Size/Code | 5.00-12 |
| Valve Code | TR-13 |
| RIM | |
| Size/Code | 4.0" x 12" |
| LOAD AND INFLATION | |
| Single | |
| Maximum Load (kg) | 620 |
| Dual | |
| Maximum Load (kg) | 600 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

LIGHT TRUCK RADIAL TYRE

EVERY JOURNEY HAS A DESTINATION



LIGHT TRUCK RADIAL TYRE

BG CARGO

Rib pattern tyre designed for better steering control & grip

Features

- Computer designed rib saw tooth
- Multi rib design
- Heat resistant tread rubber
- Flat tread

Benefits

- For smooth & quiet operation
- Enhanced added traction
- Engineered for long and even wear
- Helps maintain handling and steering control



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 145 R12 C |
| Load Index | 86 / 84 |
| Pattern | - |
| Ply Rating | 8 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 540 |
| Overall Width (mm) | 144 |
| RIM | |
| Size/Code | 4.0"J x 12" |
| LOAD AND INFLATION | |
| Single | |
| Maximum Load (kg) | 530 |
| Dual | |
| Maximum Load (kg) | 500 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

LIGHT TRUCK RADIAL TYRE

STAR SPRINTER

A radial rib type tubeless tyre for excellent drive on any surface

Features

- Special tread rubber
- Four ribs, free rolling tread with wide stabilizing shoulder
- Steel belted
- Cap ply

Benefits

- Contributes to low rolling resistance and good traction
- Allows great side wall flexibility and less internal flex heat build-up
- Radial type built for strength
- For safety and longer life

E24



PRODUCT INFORMATION

| | | |
|-------------------------------|---|-------------|
| Size | 145 R12 C | 195 R14 C |
| Load Index | 86 / 84 | 106 / 104 |
| Pattern | RIB | RIB |
| Ply Rating | 8 | 8 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 545 | 665 |
| Overall Width (mm) | 145 | 200 |
| RIM | | |
| Size/Code | 4.0"J x 12" | 5.5"J x 14" |
| LOAD AND INFLATION | | |
| Single | | |
| Maximum Load (kg) | 530 | 950 |
| Dual | | |
| Maximum Load (kg) | 500 | 900 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

LIGHT TRUCK RADIAL TYRE

BG VANO PLUS

Non directional tread pattern for powerful traction on wet surfaces specially developed for Toyota Hi ace

Features

- Durable casing
- Specially designed grooves
- Non-directional tread pattern
- Wider tyre

Benefits

- Resists nail penetration
- To make tyre more stronger & tougher
- Provides powerful traction in forward and reverse motion
- Provides better road grip on wet surfaces

E24



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 195 R15 C |
| Load Index | 107 / 105S |
| Pattern | RIB |
| Ply Rating | 8 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 690 |
| Overall Width (mm) | 192 |
| RIM | |
| Size/Code | 5.5"J x 15" |
| LOAD AND INFLATION | |
| Single | |
| Maximum Load (kg) | 975 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

LIGHT TRUCK RADIAL TYRE

BG ALRO PLUS

Multifunctional tread design provides better road grip & traction

Features

- Multifunctional tread design
- Wide circumferential grooves
- Strong casing & high endurance tyre
- Steel belted tubeless tyre

Benefits

- Provides better road grip & traction
- Provides heat and abrasion resistance
- Tough yet flexible with impact absorbing ability
- Enhanced rolling comfort & low noise



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 205/70 R15 C |
| Load Index | 106 / 104R |
| Pattern | RIB |
| Ply Rating | 8 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 670 |
| Overall Width (mm) | 205 |
| RIM | |
| Size/Code | 6.0"J x 15" |
| LOAD AND INFLATION | |
| Single Max Load (kg) | 950 |
| Dual Max Load (kg) | 900 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

4x4 RADIAL TYRE

EVERY JOURNEY HAS A DESTINATION



4x4 RADIAL TYRE

BG POWER TERRAIN

Block type pattern provides outstanding off road traction

Features

- Zigzag grooves and rough lateral blocks
- Open shoulder grooves
- Block tread design with multiple sipes
- Strong casing / high endurance tyre

Benefits

- Provides excellent traction on all kind of road conditions
- Prevents aquaplanning with enhanced wet grip performance and provides excellent water evacuation
- Provides outstanding off-road traction and reduces the risk of tread damage
- Make tyre robust and long lasting



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 205 R16 C |
| Load Index | 110 / 108 S |
| Pattern | Block |
| Ply Rating | 8 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 736 |
| Overall Width (mm) | 205 |
| RIM | |
| Size/Code | 5.5"J x 16" |
| LOAD AND INFLATION | |
| Single | |
| Max Load (kg) | 2120 |
| Dual | |
| Max Load (kg) | 4000 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

4x4 RADIAL TYRE

SUPER ALL GRIP

Radial tubeless tyre specially develop for Land Rovers

Features

- Sturdy steel belts
- Radial polyester cord body
- Heavy shoulder blocks
- Wide flat tread

Benefits

- Helps less internal flex-heat buld up due to greater side wall flexibility
- Provides cool running for extended carcass life
- Helps eject water and sand due to angle cleats
- Allows wide foot-print for road contact, excellent off-road traction

E24



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 7.50 R16 C |
| Load Index | 116 / 114 |
| Pattern | RIB/LUG |
| Ply Rating | 10 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 805 |
| Overall Width (mm) | 225 |
| RIM | |
| Size/Code | 6"J x 16" |
| LOAD AND INFLATION | |
| Single | |
| Maximum Load (kg) | 1250 |
| DUAL | |
| Maximum Load (kg) | 1120 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

SUV / CROSSOVER TYRE

EVERY JOURNEY HAS A DESTINATION



SUV / CROSSOVERS

BG RAPTOR

SUV tyre for powerful control & better road grip

Features

- Computer designed rib saw tooth
- Multi rib design
- Heat resistant tread rubber
- Flat tread

Benefits

- For smooth & quiet operation
- Enhanced added traction
- Engineered for long and even wear
- Helps maintain handling and steering control

E24



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 225/55 R18 |
| Load Index | 98 |
| Speed Rating | H |
| Pattern | RIB |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 705 |
| Overall Width (mm) | 230 |
| RIM | |
| Size/Code | 7.0"J x 18" |
| LOAD AND INFLATION | |
| Single | |
| Maximum Load (kg) | 750 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

SUV / CROSSOVERS

BG MAX SPORT

Rib pattern tyre designed for better steering control & grip

Features

- Asymmetric high performance tyre with excellent tread pattern
- 'H' rated tyre for speed upto 210 km /hr
- Joint less cap ply
- Strong casing steel belted

Benefits

- For good uniformity, steering response and even wear
- Provides smooth driving comfort
- For better ride handling and safety
- For durability and long lasting

E24



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 215/60 R17 |
| Load Index | 96 |
| Speed Rating | H |
| Pattern | RIB |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 694 |
| Overall Width (mm) | 225 |
| RIM | |
| Size/Code | 7.0" J x 17" |
| LOAD AND INFLATION | |
| Single | |
| Maximum Load (kg) | 710 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

SUV / CROSSOVERS

BG VELOTRAK PLUS

Symmetric design SUV tyre, provides better grip and style on all surfaces

Features

- High performance tyre with wide circumferential grooves
- New generation tread pattern
- Strong casing and steel belted
- With increased sipe density and braking performance
- Low noise level and low rolling resistance

Benefits

- Excellent performance on wet & dry surfaces
- Stable cornering and braking for a safely managed drive
- Ensures long life and controlled traction.
- Improved mud extraction performance and heat radiation
- Delivers optimal noise, wear and drainage performance



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 265/60 R18 |
| Load Index | 110 |
| Speed Rating | H |
| Pattern | Symmetric |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 775 |
| Overall Width (mm) | 275 |
| RIM | |
| Size/Code | 8.0J x 18" |
| LOAD AND INFLATION | |
| Single | |
| Maximum Load (kg) | 1060 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

TRUCK & BUS BIAS TYRE

EVERY JOURNEY HAS A DESTINATION



TRUCK & BUS BIAS TYRE

TRACTION RIB (TR)

The most popular rib pattern for steering truck tyres & all position bus tyres

Features

- Rib type tread
- Flat tread

Benefits

- Tough and long lasting
- Minimum heat build-up
- Excellent steerability



PRODUCT INFORMATION

| | | |
|-------------------------------|---|------------|
| Size | 8.25-20 | 10.00-20 |
| Load Range | G | H |
| Pattern | RIB | RIB |
| Ply Rating | 14 | 16 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 981 | 1080 |
| Overall Width (mm) | 280 | |
| TUBE | | |
| Size/Code | 8.25-20 | 10.00-20 |
| Valve Code | TR-77A | V3.02.15 |
| FLAP | | |
| Code | 508-190 | 508-190 |
| RIM | | |
| Size/Code | 6.5" x 20" | 7.5" x 20" |
| LOAD AND INFLATION | | |
| Single | | |
| Maximum Load (kg) | 2240 | 3000 |
| Dual | | |
| Maximum Load (kg) | 2000 | 2650 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

TRUCK & BUS BIAS TYRE

SUPER TIGER (STGR)

The ultimate tyre for long haul service

Features

- Nylon construction
- Wide deep lugs

Benefits

- For tough and long lasting service
- Light yet strong, heat resistant carcass
- Provides excellent traction in drive wheel applications



PRODUCT INFORMATION

| | | | |
|-------------------------------|---|------------|------------|
| Size | 9.00-20 | 10.00-20 | 11.00-20 |
| Load Range | H | H | H |
| Pattern | LUG | LUG | LUG |
| Ply Rating | 16 | 16 | 16 |
| MAX INFLATED DIMENSION | | | |
| Overall Diameter (mm) | 1025 | 1040 | 1100 |
| Overall Width (mm) | 255 | 272 | 295 |
| TUBE | | | |
| Size/Code | 9.00-20 | 10.00-20 | 11.00-20 |
| Valve Code | V3.02.15 | V3.02.15 | V3.05.15 |
| RIM | | | |
| Size/Code | 7.0" x 20" | 7.5" x 20" | 8.0" x 20" |
| FLAP | | | |
| Code | 508-190 | 508-190 | 502-203 |
| LOAD AND INFLATION | | | |
| Single | | | |
| Maximum Load (kg) | 2800 | 3000 | 3350 |
| Dual | | | |
| Maximum Load (kg) | 2500 | 2650 | 2900 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | | |

TRUCK & BUS BIAS TYRE

SUPER LOADER (SL)

Engineered for heavy duty services
both on highway and off the road

Features

- New generation tread design
- Wide flat trade
- Nylon construction

Benefits

- Wide flat tread design with centre rib and heavy shoulder gives strong gripping action on highway and off the road
- Tread rubber for heat resistance
- Strong body tyre that resists impact breaks



PRODUCT INFORMATION

| | | |
|-------------------------------|---|-------------|
| Size | 10.00-20 | 12.00-20 |
| Load Range | H | J |
| Pattern | RIB/LUG | RIB/LUG |
| Ply Rating | 16 | 18 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 1090 | 1122 |
| Overall Width (mm) | 295 | 306 |
| TUBE | | |
| Size/Code | 1000-20 | 12.00-20 |
| Valve Code | V3-02-15 | V3-02-15 |
| RIM | | |
| Size/Code | 7.50" x 20" | 7.50" x 20" |
| FLAP | | |
| Code | 508-190 | 508-203 |
| LOAD AND INFLATION | | |
| Single | | |
| Maximum Load (kg) | 3000 | 3750 |
| Dual | | |
| Maximum Load (kg) | 2650 | 3350 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

TRUCK & BUS BIAS TYRE

GQT

A front wheel position tyre for long haul trucks and all wheel position on buses

Features

- Tread rubber
- Rib type tread
- Strong and flexible tread rubber
- Mud and snow rated

Benefits

- Tough and long lasting
- Minimum heat build-up
- Provides excellent steerability
- All season performance



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 9.00-20 |
| Load Range | G |
| Pattern | RIB |
| Ply Rating | 14 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 1040 |
| Overall Width (mm) | 265 |
| TUBE | |
| Size/Code | 9.00-20 |
| Valve Code | TR-175A |
| RIM | |
| Size/Code | 7.0" x 20" |
| FLAP | |
| Code | 508-190 |
| LOAD AND INFLATION | |
| Single | |
| Maximum Load (kg) | 2575 |
| Dual | |
| Maximum Load (kg) | 2300 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

TRUCK & BUS BIAS TYRE

HEAVY CONTRACT TRANSPORT (HCT)

A non-directional pattern tyre for heavy duty service

Features

- Minimum heat build-up
- Strong and flexible tread rubber
- Mud & snow rated

Benefits

- Tough and long lasting
- Provides excellent steerability at front and strong traction at drive position
- Good performance in all seasons



PRODUCT INFORMATION

| | | | | |
|-------------------------------|---|------------|-------------|-----------|
| Size | 9.00-20 | 10.00-20 | 11.00-20 | 12.00-20* |
| Load Range | G | H | H | J |
| Pattern | RIB/LUG | RIB/LUG | RIB/LUG | RIB/LUG |
| Ply Rating | 14 | 16 | 12/16 | 18 |
| MAX INFLATED DIMENSION | | | | |
| Overall Diameter (mm) | 1060 | 1095 | 1120 | 1155 |
| Overall Width (mm) | 290 | 305 | 320 | |
| TUBE | | | | |
| Size/Code | 9.00-20 | 10.00-20 | 11.00-20 | 12.00-20 |
| Valve Code | TR-175A | V3.02.15 | V3.02.15 | V3.02.15 |
| RIM | | | | |
| Size/Code | 7.0"x 20" | 7.50"x 20" | 8.0"x 20" | 8.5"x 20" |
| FLAP | | | | |
| Code | 508-190 | 508-190 | 502-203 | 508-203 |
| LOAD AND INFLATION | | | | |
| Single | | | | |
| Maximum Load (kg) | 2575 | 3000 | 2725 / 3350 | 3750 |
| DUAL | | | | |
| Maximum Load (kg) | 2300 | 2650 | 2360 / 2900 | 3350 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | | | |

*Super Heavy Contract Transport (SHCT)

EXCAVATOR / OTR TYRE

EVERY JOURNEY HAS A DESTINATION



EXCAVATOR TYRE

BG SUPER EXCAVE

Powerful and durable excavator tyre for heavy construction equipment

Features

- Deep tread and thick sidewall
- Strong nylon construction
- Special ,tough & cut resistant lug tread for longer wear
- Excellent heat resistance

Benefits

- Directional tread design provides strong traction
- Specially design tyre to perform on sand, mud & rock surfaces
- Wide cleats offer outstanding traction, stability & floatation.
- Resists bruising & penetration



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 9.00-20 |
| Load Range | H |
| Pattern | LUG |
| Ply Rating | 16 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 1038 |
| Overall Width (mm) | 260 |
| TUBE | |
| Size/Code | 9.00-20 |
| Valve Code | V3-02-15 |
| RIM | |
| Size/Code | 7" x 20" |
| LOAD AND INFLATION | |
| Maximum Load (kg) | 5600 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

OTR TYRE

BG RHINO POWER

Heavy duty loader tyre for digging and load operations with excellent grip on all surfaces

Features

- Wide and flat tread area
- Stronger ply construction with robust sidewall
- Enhanced tyre wear compound
- Rounded tread contour
- Equally spaced tread grooves

Benefits

- Provides maximum ground contact
- Provides higher load stability and less tilting
- Provides maximum mileage
- Supports easy transfer of on the spot steering at high load
- Excellent self cleaning properties



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 23.5-25 |
| Load Range | N |
| Pattern | LUG |
| Ply Rating | 24 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 1575 |
| Overall Width (mm) | 575 |
| TUBE | |
| Size/Code | 23.5-25 |
| Valve Code | TRJ1175C |
| RIM | |
| Size/Code | 19.5" x 25" |
| LOAD AND INFLATION | |
| Maximum Load (kg) | 8000 @50 km/hr |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

TRACTOR FRONT & REAR TYRE

EVERY JOURNEY HAS A DESTINATION



FARM FRONT TYRE

AGRI TRAC (AT)

Front tractor tyre for MF,
Fiat and other tractors

Features

- Asymmetric design tyre with wide grooves
- Multiple circumferential ribs
- Strong casing
- Full cap ply
- H-rated steel belted tubeless tyre

Benefits

- High performance tyre in all weather conditions
- Fantastic handling & cornering characteristic
- Excellent ride comfort
- For safety & longer life
- For speed up to 210 km/hr



PRODUCT INFORMATION

| | | |
|-------------------------------|---|------------|
| Size | 6.00-16 | 7.50-16 |
| Load Range | C/D | C/D |
| Pattern | RIB | RIB |
| Ply Rating | 6/8 | 6/8 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 760 | 825 |
| Overall Width (mm) | 180 | 210 |
| TUBE | | |
| Size | 6.00-16 Fs | 7.50-16 Fs |
| Valve Code | TR-15 | TR-15 |
| RIM | | |
| Size/Code | 4.0" x 16" | 5.5" x 16" |
| LOAD AND INFLATION | | |
| Max Load (kg) | 515/615 | 670/775 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

FARM FRONT TYRE

AGRI RIB (AR)

Front position tyre for Belarus tractor

Features

- Rib-lug design
- Self cleaning design
- Tri-polymer tread compound

Benefits

- Provides excellent field steering capability and traction
- Provides self cleaning of mud
- Resists cutting, tearing and cracking



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 7.50-20 |
| Load Range | D |
| Pattern | RIB |
| Ply Rating | 8 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 910 |
| Overall Width (mm) | 205 |
| TUBE | |
| Size | 7.50-20 |
| Valve Code | TR-15 |
| RIM | |
| Size/Code | 6.0" x 20" |
| LOAD AND INFLATION | |
| Max Load (kg) | 775 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

FARM FRONT TYRE

AGRI POWER (AP)

Front tractor tyre for heavier load on all surfaces

Features

- Provides excellent field steering capability & traction
- Resists cutting, tearing & cracking
- Makes tyre robust and long lasting

Benefits

- Two block type broken rib and smart shoulder lugs
- Special tread compound
- Strong nylon construction



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 6.00-16 |
| Load Range | D |
| Pattern | RIB |
| Ply Rating | 8 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 745 |
| Overall Width (mm) | 175 |
| TUBE | |
| Size | 6.00-16 F.S |
| Valve Code | TR-15 |
| RIM | |
| Size/Code | 4.0" x 16" |
| LOAD AND INFLATION | |
| Max Load (kg) | 615 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

FARM FRONT TYRE

AGRI POWER PLUS (APP)

Front tractor tyre for heavier load

Features

- Two broken center rib and strong lugs
- Self cleaning design
- Makes tyre robust and long lasting

Benefits

- Two block type broken wide center rib and strong shoulder lugs
- Special tread compound
- Strong nylon construction



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 7.50-16 |
| Load Range | D / F |
| Pattren | RIB/LUG |
| Ply Rating | 8 / 12 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 795 |
| Overall Width (mm) | 205 |
| TUBE | |
| Size | 7.00/7.50-16 |
| Valve Code | TR-15 |
| RIM | |
| Size/Code | 5.50" x 16" |
| LOAD AND INFLATION | |
| Max Load (kg) | 775 / 950 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

FARM FRONT TYRE

AGRI GOLD (AG)

Front position tyre for Belarus tractor

Features

- Two broken center rib and strong lugs
- Self cleaning design
- Strong nylon construction

Benefits

- For excellent non-slip & long wearing performance
- Provides cleaning of muds/sand
- Makes tyre robust & long lasting



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 9.00-20 |
| Load Range | F |
| Pattren | RIB/LUG |
| Ply Rating | 12 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 955 |
| Overall Width (mm) | 225 |
| TUBE | |
| Size | 9.00-20 |
| Valve Code | TR-15 |
| RIM | |
| Size/Code | 5.5" x 20" |
| LOAD AND INFLATION | |
| Max Load (kg) | 1120 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

FARM REAR TYRE

POWER LUG (PL)

Original OEM rear tyre for MF, New Holland and other tractors

Features

- Big and tough super heavy-weight tread
- Nylon body
- Husky under-tread
- Wide cleats
- Open centre design

Benefits

- Extra weight stops wheel spinning
- Maximises load carrying ability
- Resists bruising and penetration
- Wide cleats offer outstanding traction, stability and floatation
- Ensures excellent traction, stability and floatation



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 12.4/11-28 |
| Load Range | C/D |
| Pattern | LUG |
| Ply Rating | 6/8 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 1275 |
| Overall Width (mm) | 325 |
| TUBE | |
| Size | 12.4/11-28 |
| Valve Code | 218A |
| RIM | |
| Size/Code | 11.00" x 28" |
| LOAD AND INFLATION | |
| Max Load (kg) | 1150/1355 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

FARM REAR TYRE

SUPER POWER LUG (SPL)

Original OEM rear tyre for MF, New Holland and other tractors

Features

- Big and tough super heavy-weight tread
- Nylon body
- Husky under-tread
- Wide cleats
- Open centre design

Benefits

- Extra weight stops wheel spinning
- Maximises load carrying ability
- Resists bruising and penetration
- Wide cleats offer outstanding traction, stability and floatation
- Ensures excellent traction, stability and floatation



PRODUCT INFORMATION

| | | |
|-------------------------------|---|--------------|
| Size | 12.4/11-28 | 14.9/13-28 |
| Load Range | D | C/D |
| Pattern | LUG | LUG |
| Ply Rating | 8 | 6/8 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 1275 | 1375 |
| Overall Width (mm) | 325 | 360 |
| TUBE | | |
| Size | 12.4/11-28 | 14.9/13-28 |
| Valve Code | TR-218A | TR-218A |
| RIM | | |
| Size/Code | 11.00" x 28" | 13.00" x 28" |
| LOAD AND INFLATION | | |
| Max Load (kg) | 1355 | 1450 / 1700 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

FARM REAR TYRE

AGRI LUG

Rear tractor tyre for farm service

Features

- Specially made design / pattern for farm service
- Nylon body
- Comparative low weight
- Strong carcass

Benefits

- Provides good performance in the field
- Provides excellent traction and floatation
- Low fuel consumption
- Helps resist bruising and penetration
- Economical Tyre



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 124 / 11-28 |
| Load Range | C |
| Pattern | LUG |
| Ply Rating | 6 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 1242 |
| Overall Width (mm) | 315 |
| TUBE | |
| Size/Code | 124 / 11-28 |
| Valve Code | TR-218 A |
| RIM | |
| Size/Code | 11.00" x 28" |
| LOAD AND INFLATION | |
| Single | |
| Maximum Load (kg) | 1150 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

FARM REAR TYRE

BLACK BULL

Rear Tractor Tyre For Heavier Load
on All Surfaces

Features

- Tough heavy weight tread
- Strong nylon casing
- Husky under tread
- Open center design
- Specially designed angular lugs

Benefits

- Extra weight helps prevent wheel spinning
- Ability to carry heavier loads on hard surfaces
- Helps resist bruising and penetration
- Ensures excellent traction, stability floatation and uniform wear



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 12.4 - 28 |
| Load Range | F |
| Pattern | LUG |
| Ply Rating | 12 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 1284 |
| Overall Width (mm) | 332 |
| TUBE | |
| Size | 12.4/11-28 |
| Valve Code | TR-218A |
| RIM | |
| Size/Code | 11.00" x 28" |
| LOAD AND INFLATION | |
| Max Load (kg) | 1550 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

FARM REAR TYRE

DOUBLE BULL POWER (DBP)

Rear Tractor Tyre For Heavier Load on All Surfaces

Features

- Reinforced, strong and big tyre
- Robust in design and construction
- Stronger Nylon casing for less wear
- Specially designed strong based deep angular lugs
- Heavy duty tyre

Benefits

- Improved lug contact area for improved traction
- Economical due to low slippage in field use
- Extra weight helps prevent wheel spinning
- Husky undertread helps resist bruising and penetration
- Excellent self cleaning properties



PRODUCT INFORMATION

| | | | |
|-------------------------------|---|------------|------------|
| Size | 14.9-28 | 13.6-28 | 18.4-30 |
| Load Range | F | F | J |
| Pattern | LUG | LUG | LUG |
| Ply Rating | 12 | 12 | 18 |
| MAX INFLATED DIMENSION | | | |
| Overall Diameter (mm) | 1420 | 1362 | 1552 |
| Overall Width (mm) | 390 | 355 | 492 |
| TUBE | | | |
| Size | 14.9/11-28 | 13.6/11-28 | 18.4/15-30 |
| Valve Code | TR-218A | TR-218A | TR-218A |
| RIM | | | |
| Size/Code | 11"x 28" | 11"x 28" | 14"x 30" |
| LOAD AND INFLATION | | | |
| Max Load (kg) | 2120 | 2120 | 3340 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | | |

FARM REAR TYRE

SUPER ALL GRIP TRACTION (SAGT)

Original OEM rear tyre for
MF and New Holland heavy tractors

Features

- Big and tough super heavy weight tread
- Wide cleats
- Nylon body
- Husky undertread

Benefits

- Extra weight helps stop wheel spinning
- Wide cleats offer outstanding traction, stability and floatation
- Maximises load carrying ability
- Resists bruising and penetration



PRODUCT INFORMATION

| | | |
|-------------------------------|---|------------|
| Size | 16.9/14-30 | 18.4/15-30 |
| Load Range | D/C | D/C |
| Pattren | LUG | LUG |
| Ply Rating | 8/14 | 8/14 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 1510 | 1570 |
| Overall Width (mm) | 420 | 470 |
| TUBE | | |
| Size | 16.9/14-30 | 18.4/15-30 |
| Valve Code | TR-218A | TR-218A |
| RIM | | |
| Size/Code | 14" x 30" | 15" x 30" |
| LOAD AND INFLATION | | |
| Max Load (kg) | 2000/2725 | 2180/3250 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

FARM REAR TYRE

POWER LUG PLUS (PLP)

Rear tractor robust tyre for excellent performance

Features

- Extra load carrying capacity
- Extra weight stops wheel spinning
- Extra mileage & long life
- Extra load carrying capacity
- Resist bruising and penetration

Benefits

- Big, Strong and robust tyre
- Nylon body
- Very good traction due to deep lugs and good self-cleaning
- Wide cleats
- Open center design



PRODUCT INFORMATION

| | | |
|-------------------------------|---|-----------|
| Size | 15.5 -38 | 16.9-38 |
| Load Range | F | F |
| Pattren | LUG | LUG |
| Ply Rating | 12 | 12 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 1615 | 1705 |
| Overall Width (mm) | 390 | 425 |
| TUBE | | |
| Size | 15.5-38 | 16.9-38 |
| Valve Code | TR-184A | TR-218A |
| RIM | | |
| Size/Code | 14" x 38" | 14" x 38" |
| LOAD AND INFLATION | | |
| Max Load (kg) | 2220 | 3050 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

MOTORCYCLE TYRE

EVERY JOURNEY HAS A DESTINATION



MOTORCYCLE FRONT TYRE FOR 70CC

DURO GRIP

Rib type pattern provides excellent road grip

Features

- Rib type pattern
- Strong nylon carcass
- Specially developed tread compound

Benefits

- For excellent road grip
- For durability & longlife
- Provides endurance, reliability & economy



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 2.25 - 17F |
| Load Range | C |
| Ply Rating | 6 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 565 |
| Overall Width (mm) | 60 |
| TUBE | |
| Size | 2.25/2.50 - 17 |
| Valve Code | TR - 4 |
| RIM | |
| Size | 1.2" x 17" |
| LOAD AND INFLATION | |
| Max Load (kg) | 132 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

MOTORCYCLE TYRE FOR 70CC

DURO GRIP

Better fuel economy & cool running tyre

Features

- Specially designed pattern
- Wide, deep, see-through channels with deep sipes
- Special recipe for tread/carcass compound

Benefits

- For comfortable ride in all seasons
- Good performance in wet & dry conditions
- For cool running, less heat build-up & durability



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 2.50 - 17R |
| Load Range | C |
| Ply Rating | 6 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 568 |
| Overall Width (mm) | 62 |
| TUBE | |
| Size | 2.25/2.50 - 17 |
| Valve Code | TR - 4 |
| RIM | |
| Size | 1.4" x 17" |
| LOAD AND INFLATION | |
| Max Load (kg) | 155 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

MOTORCYCLE FRONT TYRE FOR 70CC & 125CC

HYPER SONIC

Front tyre for excellent grip

Features

- Rib type pattern
- Strong nylon carcass
- Specially developed tread compound

Benefits

- Provides excellent grip, precise response & support for wet traction
- For high endurance & better reliability
- For long life, better mileage & cool running



PRODUCT INFORMATION

| | | |
|-------------------------------|---|----------------|
| Size | 2.25 - 17F | 2.50 - 18F |
| Load Range | C | C |
| Ply Rating | 6 | 6 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 570 | 598 |
| Overall Width (mm) | 64 | 63 |
| TUBE | | |
| Size | 2.25 / 2.50 - 18 | 2.50/2.75 - 18 |
| Valve Code | TR - 4 | TR - 4 |
| RIM | | |
| Size | 1.2" x 17" | 1.4" x 18" |
| LOAD AND INFLATION | | |
| Max Load (kg) | 155 | 164 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

MOTORCYCLE TYRE FOR 70CC & 125CC

HYPER SONIC

For a better & comfortable ride

Features

- Specially designed pattern
- Wide, deep, see-through channels with deep sipes
- Special recipe for tread/carcass compound

Benefits

- For comfortable ride in all seasons
- Good performance in wet & dry conditions giving longer life
- For cool running, less heat build up & durability



PRODUCT INFORMATION

| | | | |
|-------------------------------|---|----------------|--------------|
| Size | 2.50 - 17R | 3.00 - 17R | 2.75-18R |
| Load Range | C | C | C |
| Ply Rating | 6 | 6 | 6 |
| MAX INFLATED DIMENSION | | | |
| Overall Diameter (mm) | 568 | 598 | 614 |
| Overall Width (mm) | 62 | 77 | 72 |
| TUBE | | | |
| Size | 2.25/2.50 - 17 | 2.75/3.00 - 17 | 2.50/2.75-18 |
| Valve Code | TR - 4 | TR - 4 | TR-4 |
| RIM | | | |
| Size | 1.4" x 17" | 1.6" x 17" | 1.6" x 18" |
| LOAD AND INFLATION | | | |
| Max Load (kg) | 155 | 190 | 180 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | | |

MOTORCYCLE TYRE FOR 70CC & 125CC

BLACK COBRA

Directional pattern for style and better road grip

Features

- New generation tread design
- Directional designed pattern
- Wide serrated shoulder rib
- Special recipe for tread / carcass compound
- Strong nylon carcass

Benefits

- Ensures better precision, good traction & optimised wear
- For high performance and low noise
- Provides excellent floatation, powerful turning control and remarkable traction
- For cool running, less heat build up & durability
- Better endurance and reliability



PRODUCT INFORMATION

| | | |
|-------------------------------|---|----------------|
| Size | 2.50 - 17R | 3.00 - 17R |
| Load Range | C | C |
| Ply Rating | 6 | 6 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 573 | 598 |
| Overall Width (mm) | 62 | 76 |
| TUBE | | |
| Size | 2.25/2.50 - 17 | 2.75/3.00 - 17 |
| Valve Code | TR - 4 | TR - 4 |
| RIM | | |
| Size | 1.4" x 17" | 1.6" x 17" |
| LOAD AND INFLATION | | |
| Max Load (kg) | 155 | 190 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

MOTORCYCLE TYRE FOR 70CC

AQUA GRIP

Aqua planning wide and deep channels enhance water evacuation for a better grip

Features

- Specially designed pattern for all seasons
- Wide & deep channels for aqua planning
- Special recipe for tread/carcass compound

Benefits

- Good performance tyre in all seasons
- Enhances water evacuation for a better grip
- Excellent ride comfort
- High endurance and better mileage tyre



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 2.50 - 17R |
| Load Range | C/D |
| Ply Rating | 6/8 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 570 |
| Overall Width (mm) | 65 |
| TUBE | |
| Size | 2.25/2.50 - 17 |
| Valve Code | TR-4 |
| RIM | |
| Size | 1.4" x 17" |
| LOAD AND INFLATION | |
| Max Load (kg) | 155 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

MOTORCYCLE TYRE FOR 70CC

NIAGARA XP

All season tyre for excellent ride comfort and better mileage

Features

- Specially designed pattern for local conditions
- Wide and deep channels with sipes
- Strong nylon casing

Benefits

- Good performance tyre in all seasons
- Excellent ride comfort
- High endurance and better mileage tyre



PRODUCT INFORMATION

| | | |
|-------------------------------|---|----------------|
| Size | 2.50 - 17R | 2.75 - 18R |
| Load Range | C | C/D |
| Ply Rating | 6 | 6/8 |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 570 | 618 |
| Overall Width (mm) | 65 | 73 |
| TUBE | | |
| Size | 2.25/2.50 - 17 | 2.50/2.75 - 18 |
| Valve Code | TR - 4 | TR - 4 |
| RIM | | |
| Size | 1.4" x 17" | 1.8" x 18" |
| LOAD AND INFLATION | | |
| Max Load (kg) | 155 | 180 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

MOTORCYCLE TYRE FOR 125CC

CLIFF RIDE

High endurance tyre provides excellent road grip

Features

- Specially designed pattern for different terrains
- Wide center rib with strong shoulder lugs
- Strong nylon casing

Benefits

- Provides excellent road grip on different surfaces
- For cool running
- Makes the tyre more durable



PRODUCT INFORMATION

| | | |
|-------------------------------|---|----------------|
| Size | 2.50 - 18F | 2.75 - 18F |
| Load Range | C | C |
| Ply Rating | 6 | 6 |
| Approx Weight | - | - |
| MAX INFLATED DIMENSION | | |
| Overall Diameter (mm) | 598 | 612 |
| Overall Width (mm) | 65 | 72 |
| TUBE | | |
| Size | 2.50/2.75 - 18 | 2.50/2.75 - 18 |
| Valve Code | TR - 4 | TR - 4 |
| Approx Weight | - | - |
| RIM | | |
| Size | 1.6" x 18" | 1.6" x 18" |
| LOAD AND INFLATION | | |
| Max Load (kg) | 180 | 180 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations | |

MOTORCYCLE TYRE FOR 70CC

HARFUN XP

Directional pattern tyre for style and performance

Features

- New generation attractive tread design
- Directional tyre
- Strong shoulder with wide groove
- Special recipe for tread/carcass compound
- Strong nylon carcass

Benefits

- Ensures better precision, good traction & optimised wear
- For high performance and low noise
- For cool running, less heat build up & durability
- Better endurance and reliability



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 2.50 - 17R |
| Load Range | C/D |
| Ply Rating | 6/8 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 570 |
| Overall Width (mm) | 64 |
| TUBE | |
| Size | 2.25/2.50 - 17 |
| Valve Code | TR - 4 |
| RIM | |
| Size | 1.4" x 17" |
| LOAD AND INFLATION | |
| Max Load (kg) | 155 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

MOTORCYCLE TYRE FOR 70CC

SNAKE EYES

Directional Tyre Provides Good Traction on all surfaces

Features

- New generation tread design / pattern
- Strong nylon carcass
- Special recipe for tread / carcass compound
- Directional tyre

Benefits

- Provides good traction
- For durability and long life
- Cool running and less heat build up
- For comfortable ride in all season



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 2.50 - 17R |
| Load Range | C |
| Ply Rating | 6 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 570 |
| Overall Width (mm) | 64 |
| TUBE | |
| Size | 2.25/2.50 - 17 |
| Valve Code | TR - 4 |
| RIM | |
| Size | 1.4" x 17" |
| LOAD AND INFLATION | |
| Max Load (kg) | 155 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

MOTORCYCLE TYRE FOR 125CC

SPYDER WEB

High endurance tyre provides excellent road grip

Features

- New generation tread design
- Directional pattern tyre
- Strong shoulder with wide groove
- Special recipe for tread / carcass compound
- Strong nylon carcass

Benefits

- Ensure good traction and optimised wear
- For comfortable ride in all seasons
- For better road grip
- High endurance and reliability



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 3.00 - 17R |
| Load Range | C/D |
| Ply Rating | 6/8 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 598 |
| Overall Width (mm) | 76 |
| TUBE | |
| Size | 2.75/3.00 - 17 |
| Valve Code | TR - 4 |
| RIM | |
| Size | 1.6" x 17" |
| LOAD AND INFLATION | |
| Max Load (kg) | 190 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

MOTORCYCLE TYRE FOR 125CC

GOTO GOLD

For a better & comfortable ride

Features

- New generation tread design.
- Directional pattern.
- Strong nylon carcass.
- Specially developed tread compound.

Benefits

- Ensures better handling, good traction and optimized wear.
- For better performance and low noise.
- Better endurance and reliability.
- For long life, better mileage and cool running.



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 3.00-17R |
| Load Range | C |
| Ply Rating | 6 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 598 |
| Overall Width (mm) | 77 |
| TUBE | |
| Size | 2.75/3.00-17 |
| Valve Code | TR -04 |
| RIM | |
| Size | 1.6" x 17" |
| LOAD AND INFLATION | |
| Max Load (kg) | 180 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

MOTORCYCLE TYRE FOR 125CC

CHALLENGER

For a better & comfortable ride

Features

- New generation directional tread design.
- Specially Designed tread pattern.
- Special recipe for tread/carcass compound.
- Strong nylon carcass.

Benefits

- Ensures better handling, good traction and optimized wear.
- For high performance and low noise.
- Better endurance and reliability.
- For cool running, less heat build up & durability.



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 2.75-18F |
| Load Range | C |
| Ply Rating | 6 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 612 |
| Overall Width (mm) | 70 |
| TUBE | |
| Size | 2.50/2.75-18 |
| Valve Code | TR -04 |
| RIM | |
| Size | 1.6" x 18" |
| LOAD AND INFLATION | |
| Max Load (kg) | 180 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

MOTORCYCLE TYRE FOR 125CC

GOTO GRIP

Designed to perform on all surfaces

Features

- New generation tread design
- Wide and deep angular channel
- Special recipe for tread / carcass compound
- Kerbing band
- Strong nylon carcass

Benefits

- Ensures better handling, good traction & optimized wear
- For better performance and low noise
- Good performance in wet and dry surfaces
- Cooler running and durability
- Better endurance and reliability



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 90/90 - 18 |
| Load Range | C |
| Ply Rating | 6 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 625 |
| Overall Width (mm) | 75 |
| TUBE | |
| Size | 90/90-18 |
| Valve Code | TR-04 |
| RIM | |
| Size | 2.0" x 18" |
| LOAD AND INFLATION | |
| Max Load (kg) | 195 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

MOTORCYCLE TYRE FOR 125CC

MUSTANG

Directional pattern tyre for excellent traction

Features

- New generation tread design
- Directional designed pattern
- Wide & deep angular channel
- Special recipe for tread / carcass compound
- Kerbing band
- Strong nylon carcass

Benefits

- Ensures better handling, good traction & optimized wear
- For better performance and low noise
- Good performance in wet & dry surfaces. Gives good mileage
- For cool running, less heat build up & durability
- Protects sidewall from damage
- Better endurance & reliability



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 2.50 - 17R |
| Load Range | C |
| Ply Rating | 6 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 573 |
| Overall Width (mm) | 62 |
| TUBE | |
| Size | 2.25/2.50 - 17 |
| Valve Code | TR - 4 |
| RIM | |
| Size | 1.4" x 17" |
| LOAD AND INFLATION | |
| Max Load (kg) | 155 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

MOTORCYCLE TYRE FOR 70CC

TUFF RIDER

Directional pattern tyre for excellent traction

Features

- Specially designed directional tubeless tyre
- Special recipe for tread & carcass compound
- New generation design pattern.
- Optimized channel with deep sipes

Benefits

- Comfortable ride and low noise
- High air retentivity for longer period
- Provides cool running & less heat build up
- Good performance in wet and dry season



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 2.50 - 17F |
| Load Range | C |
| Ply Rating | 6 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 570 |
| Overall Width (mm) | 65 |
| TUBE | |
| Size | 2.50/2.75-17 |
| Valve Code | TR-4 |
| RIM | |
| Size | 1.4" x 17" |
| LOAD AND INFLATION | |
| Max Load (kg) | 155 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

MOTORCYCLE TYRE FOR 70CC

SANGEE

Block type pattern for comfortable ride in all seasons

Features

- Specially designed directional tubeless tyre
- Special recipe for tread & carcass compound
- Special block type pattern
- Optimized channel with deep sipes

Benefits

- Comfortable ride and low noise
- High air retentivity for longer period
- Provides cool running & less heat build up
- Good performance in wet and dry season



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 2.50 - 17R |
| Load Range | C |
| Ply Rating | 6 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 570 |
| Overall Width (mm) | 64 |
| TUBE | |
| Size | 2.25/5.50 - 17 |
| Valve Code | TR-4 |
| RIM | |
| Size | 1.4" x 17" |
| LOAD AND INFLATION | |
| Max Load (kg) | 155 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

MOTORCYCLE TYRE FOR 125CC

JANNAN

Directional pattern for better handling
and cool running

Features

- New generation tread design
- Directional pattern
- Strong nylon carcass
- Specially developed tread compound

Benefits

- Ensures better handling, good traction and optimized wear
- For better performance and low noise
- Better endurance and reliability
- For long life, better mileage and cool running



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 2.50 - 18F |
| Load Range | C |
| Ply Rating | 6 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 598 |
| Overall Width (mm) | 63 |
| TUBE | |
| Size | 2.50/2.75 - 18 |
| Valve Code | TR - 4 |
| RIM | |
| Size | 1.4" x 18" |
| LOAD AND INFLATION | |
| Max Load (kg) | 164 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

MOTORCYCLE TYRE FOR 70CC

MAGNETO

New generation directional pattern tyre
for style and performance

Features

- New generation directional tread design
- Specially designed tread pattern
- Wide circumferential groove
- Specially developed wear resistance tread compound
- Attractive off shoulder area

Benefits

- Provides excellent grip and powerful turning control
- Exceptional handling for better steering stability
- Provides excellent traction in all weather conditions
- For longer life and more mileage in all seasons
- Enhanced durability and tread wear



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 2.50 - 17R |
| Load Range | C |
| Ply Rating | 6 |
| Design | Magneto |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 568 |
| Overall Width (mm) | 62 |
| TUBE | |
| Size | 2.50/2.50 - 17 |
| Valve Code | TR - 4 |
| RIM | |
| Size | 1.4" x 17" |
| LOAD AND INFLATION | |
| Max Load (kg) | 155 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

MOTORCYCLE TYRE FOR 70CC

JUNGLE JIM

Reinforced all terrain pattern
tyre for better performance

Features

- Deep, aggressive, serrated block and reinforced pattern
- Specially designed wide and compact tread
- Well designed/decorated off shoulder area
- Strong nylon carcass
- Specially developed wear resistance tread compound

Benefits

- Excellent for all terrain services and equally good for roads
- Provides wide footprint for traction and road grip
- For cool running and less heat build up
- Better endurance and reliability
- For longer life and more mileage in all seasons



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 2.50 - 17R |
| Load Range | C |
| Ply Rating | 6 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 570 |
| Overall Width (mm) | 62 |
| TUBE | |
| Size | 2.25/2.50 - 17 |
| Valve Code | TR - 4 |
| RIM | |
| Size | 1.4" x 17" |
| LOAD AND INFLATION | |
| Max Load (kg) | 155 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

RICKSHAW TYRE

EVERY JOURNEY HAS A DESTINATION



RICKSHAW FRONT TYRE

CHIEF

Durable and more fuel efficient
on all road surfaces

Features

- Resilient cord body
- Strong bonding between rubber and fabric
- Tough yet flexible
- Low rolling resistance

Benefits

- Resists bruise impact
- Provides more strength to the body
- Excellent stability
- Helps in hydroplaning with better fuel economy



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 4.00 - 8F |
| Load Range | D |
| Ply Rating | 8 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 417 |
| Overall Width (mm) | 110 |
| TUBE | |
| Size | 4.00 - 8 |
| Valve Code | JS-87C |
| RIM | |
| Size | 2.50" x 8" |
| LOAD AND INFLATION | |
| Max Load (kg) | 400 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

RICKSHAW REAR TYRE

CHIEF

Durable and more fuel efficient
on all road surfaces

Features

- Tough and long wearing tread rubber
- Strong nylon carcass
- Powerful and deep shoulder

Benefits

- For cool running and durability
- Good performance in wet and dry conditions
- Provides extra traction in sand and mud



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 4.00 - 8R |
| Load Range | D |
| Ply Rating | 8 |
| Pattern | LUG |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 420 |
| Overall Width (mm) | 110 |
| TUBE | |
| Size | 4.00 - 8 |
| Valve Code | JS-87C |
| RIM | |
| Size | 2.50" x 8" |
| LOAD AND INFLATION | |
| Max Load (kg) | 400 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

CNG RICKSHAW TYRE

CHIEF

Reliable and durable on all road surfaces

Features

- Resilient cord body
- Strong bonding between rubber & fabric
- Tough yet flexible
- Modern design with sipes
- Low rolling resistance

Benefits

- Resists bruise impact
- Provides more strength to the body
- Excellent stability
- Helps in hydroplaning
- Better fuel efficiency



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Size | 135 - 10 |
| Pattren | RIB |
| Ply Rating | 10 |
| Load Index | 81 |
| MAX INFLATED DIMENSION | |
| Overall Diameter (mm) | 515 |
| Overall Width (mm) | 130 |
| TUBE | |
| Size | 135 - 10 |
| Valve Code | TR-13 |
| RIM | |
| Size | 3.50" x 10" |
| LOAD AND INFLATION | |
| Max Load (kg) | 460 |
| Air Pressure (PSI) | Follow Vehicle Manufacturer's Recommendations |

TYRE CARE

Air Pressure

Correct level of tyre pressure is vital. Consult your vehicle owner's manual about the required pressure recommended by the manufacturer and get the inflation checked at regular intervals, preferably from same filling station. While driving on highways or motorways at higher than normal speed, ensure that your tyres have approximately 3 psi more pressure than normal. Revert back to normal pressure in the city.

Rotation

It is necessary to rotate the tyres after every 10,000 kilometers for even wear and longer life.

Balancing

Always get your tyre/wheel assembly dynamically balanced for a comfortable and smooth ride.

Wheel Alignment

Misaligned tyre leads to higher fuel consumption, less driving comfort. Check wheel alignment every six months.

Driving Habits

Drive consistently, accelerate and brake gradually and smoothly.

UNDERSTANDING TYRES

Tyre Construction

Tyres are classified according to their construction as:



- 1- Radial
- 2- Bias or Diagonal or Cross Ply

Radial Construction

In a Radial tyre, ply cord, either steel or fabric, run straight across the tyre from bead to bead. In addition, the radial tyre has a belt of additional plies, usually steel running down the centre of the tyre between the carcass and the tread. This construction allows the radial sidewall to be much more flexible while the tread is much stiffer than bias ply tyres. This allows the tyre to absorb impacts and limit sideways movement of the tread while cornering.

Bias Construction

In the Bias ply tyre, also known as diagonal ply tyre, plies run from bead to bead at an angle (hence the name bias). With layers of plies criss-crossing each other, this construction makes the sidewall relatively stiffer and the tread area softer.



KNOWING YOUR TYRE

You may wish to know what size tyre you use. You can get the tyre's size by reading the sidewall.

The Numbers / Lettering stands for:

215 = Width of the tyre in millimetres
 55 = Height of the tyre sidewall as a percentage of the width, also known as the aspect ratio
 R = Radial construction
 16 = The diameter of the wheel
 93 = Load carrying capacity of tyre
 H = Speed Symbol indicates the max. speed (210 km/hr) for the tyre at full load.

32 = Week of manufacturing
 22 = Year of manufacturing



Manufacturing Date



Tyre Load Range

| Load Range & Ply Rating | |
|-------------------------|---------------|
| A | 2 Ply Rating |
| B | 4 Ply Rating |
| C | 6 Ply Rating |
| D | 8 Ply Rating |
| E | 10 Ply Rating |
| F | 12 Ply Rating |
| G | 14 Ply Rating |
| H | 16 Ply Rating |
| J | 18 Ply Rating |


Tyre Speed Ratings

| Ratings for KM Per Hour | |
|-------------------------|-----------------|
| P | Up to 150 km/hr |
| Q | Up to 160 km/hr |
| R | Up to 170 km/hr |
| S | Up to 180 km/hr |
| T | Up to 190 km/hr |
| U | Up to 200 km/hr |
| H | Up to 210 km/hr |
| V | Up to 240 km/hr |
| W | Up to 270 km/hr |
| Y | Up to 300 km/hr |
| ZR | Over 250 km/hr |

Load Carrying Capacity

| Load Index | Load Carrying Capacity (kgs) |
|------------|------------------------------|
| 73 / 69 | 365 / 325 |
| 75 / 74 | 387 / 375 |
| 79 / 77 | 437 / 412 |
| 83 / 82 | 487 / 475 |
| 86 / 84 | 530 / 500 |
| 91 / 89 | 615 / 580 |
| 102 / 100 | 850 / 800 |
| 106 / 104 | 950 / 900 |
| 116 / 114 | 1250 / 1180 |

* European Tyre & Rim Technical Organization Standard Manual 2005





EVERY **JOURNEY**
HAS A **DESTINATION**



EVERY **JOURNEY**
HAS A **DESTINATION**

GHANDHARATYRE AND RUBBER COMPANY LIMITED

(formerly known as The General Tyre and Rubber Company
of Pakistan Limited)

HEAD OFFICE/FACTORY

H-23/2, Landhi Industrial Trading Estate,
Landhi, Karachi, Pakistan
Phone: +92 21 3508 0172 (10 Lines)
UAN: +92 21 111 487 487
Fax: +92 21 3508 0171 - +92 21 3508 3606
Email: headoffice@gentipak.com

ISLAMABAD OFFICE

Plot No. 148-149, Khuda Bakhsh Road, Saraan,
Kahuta Industrial Triangle, Kahuta Road, Hummak Islamabad
Phone: +92 51-5971612-13 / 51-5971650
UAN: +92 51 111 487 487
Fax: +92 51-597 1615
Email: islamabad@gentipak.com

LAHORE OFFICE/SALES & SERVICE CENTRE

20, Shahrah-e-Fatimah Jinnah Road,
Near Ganga Ram Hospital,
Lahore, Pakistan
Phone: +92 42 3630 8605 - 07 / 363 00105-07
UAN: +92 42 111 487 487
Fax: +92 42 363 00108
Email: lahore@gentipak.com

MULTAN OFFICE

Plot No. 758 - 759/21,
Khanewal Road, Multan, Pakistan
Phone: +92 61 677 4407 - 8, +92 61 678 0757-58
Fax: +92 61 455 0800
Email: gtrmultan@gentipak.com

SUKKUR OFFICE

Plot No. B 30/8, SITE Area, Sukkur
Phone: +92 300 0562502



GTRTyre



GTRTyre



GTRTyre

www.gtr.com.pk